

Nomenclature

Roman Letters

a	Amplitude of wave-like disturbance
A	Cross-sectional area or cloud radius
\mathcal{A}	Attenuation
b	Thickness
b	Power law index
Ba	Bagnold number, $\rho_S D^2 \dot{\gamma} / \mu_L$
c	Concentration
c	Speed of sound
c_p	Specific heat at constant pressure
c_s	Specific heat of solid or liquid
c_v	Specific heat at constant volume
c_κ	Phase velocity for wavenumber κ
$C, C_1, C_2, C_R, etc.$	Constants
C	Compliance
C	Damping coefficient
C_D	Drag coefficient
C_L	Lift coefficient
C_{ij}	Drag and lift coefficient matrix
C_p	Coefficient of pressure
C_{pmin}	Minimum coefficient of pressure
d	Diameter
d_j	Jet diameter
d_o	Hopper opening diameter
D	Particle, droplet or bubble diameter
D	Mass diffusivity
D_h	Hydraulic diameter
D_m	Volume (or mass) mean diameter
D_s	Sauter mean diameter
$D(T)$	Determinant of the transfer matrix $[T]$
\mathcal{D}	Thermal diffusivity
e	Specific internal energy
e_{ij}	Rate of strain tensor
E	Young's modulus of elasticity
E_{ij}	Strain tensor
\mathcal{E}	Rate of exchange of energy per unit volume
f	Frequency in Hz
\hat{f}	Radian frequency, $2\pi f$
f	Friction factor
\underline{f}, f_i	Body force per unit volume
f_L, f_V	Liquid and vapor thermodynamic quantities

F_i	Force vector
Fr	Froude number
\mathcal{F}	Interactive force per unit volume
g	Acceleration due to gravity
g_L, g_V	Liquid and vapor thermodynamic quantities
G	Shear modulus of elasticity
G_{Ni}	Mass flux of component N in direction i
G_N	Mass flux of component N
h	Specific enthalpy
h^*	Specific total enthalpy
h	Heat transfer coefficient
h	Height
H	Total head, $p^T/\rho g$
H	Height
H	A boundary layer profile parameter
ΔH	Total head difference
He	Henry's law constant
Hm	Haberman-Morton number, normally $g\mu^4/\rho S^3$
i, j, k, m, n	Indices
i	Square root of -1
I	Acoustic impulse
\mathcal{I}	Rate of transfer of mass per unit volume
j_i	Total volumetric flux in direction i
j_{Ni}	Volumetric flux of component N in direction i
j_N	Volumetric flux of component N
k	Polytropic constant
k	Thermal conductivity
k	Boltzmann's constant
k_L, k_V	Liquid and vapor quantities
K	Hydraulic loss coefficient
K	Constant
K^*	Cavitation compliance
Kc	Keulegan-Carpenter number
K_{ij}	Added mass coefficient matrix
K_n, K_s	Elastic spring constants in normal and tangential directions
Kn	Knudsen number, $\lambda/2R$
\mathcal{K}	Frictional constants
l	Typical dimension
l	Mean free path
l_t	Turbulent length scale
L	Length
L	Inertance
\mathcal{L}	Latent heat
m	Mass flow rate
\dot{m}	Mass flow rate
m_G	Mass of gas in bubble
m_p	Mass of particle
M	Mass
M	Mach number

M^*	Mass flow gain factor
M_{ij}	Added mass matrix
\mathcal{M}	Molecular weight
Ma	Martinelli parameter
n	Number of particles per unit volume
n	Normal coordinate
\underline{n}	Unit normal vector
\dot{n}	Number of events per unit time
n_i	Unit vector in the i direction
$N(R), N(D), N(v)$	Particle size distribution functions
N^*	Number of sites per unit area
Nu	Nusselt number, hD_h/k_L
p	Pressure
p^T	Total pressure
p_a	Radiated acoustic pressure
p_G	Partial pressure of gas
p_s	Sound pressure level
p_V	Vapor pressure
P	Perimeter
P	Power
\mathcal{P}	Perimeter
Pe	Peclet number, usually WR/α_C
Pm	Prandtl-Meyer function, in degrees
Pr	Prandtl number, $\rho\nu c_p/k$
q	General variable
\tilde{q}^n	Vector of fluctuating quantities
q	Heat flux per unit surface area
q_i	Heat flux vector
Δq	Heat added per unit mass
Q	Volume flow rate
Q	General variable
\mathcal{Q}	Rate of heat production per unit length
\mathcal{Q}	Rate of heat transfer or release per unit mass
\mathcal{Q}_ℓ	Rate of heat addition per unit length of pipe
r, r_i	Radial coordinate and position vector
r_d	Impeller discharge radius
r, θ, z	Cylindrical coordinates
r, θ, ϕ	Spherical coordinates
R	Sphere, bubble, particle or droplet radius
R	Resistance
R_k^*	Resistance of component, k
R_B	Equivalent volumetric radius, $(3\tau/4\pi)^{1/3}$
R_e	Equilibrium radius
Re	Reynolds number
\mathcal{R}	Gas constant
s	Coordinate measured along a streamline or pipe centerline
s, n	Tangential and normal coordinates
s	Laplace transform variable
s	Specific entropy

S	Surface tension
S_D	Surface of the disperse phase
St	Stokes number
Str	Strouhal number
t	Time
t_c	Binary collision time
t_u	Relaxation time for particle velocity
t_T	Relaxation time for particle temperature
T	Temperature
T	Granular temperature
T	A boundary layer profile parameter
T_{ij}	Transfer matrix
\mathcal{T}	Torque coefficient
u	Fluid velocity
u, v, w	Fluid velocity components in Cartesian coordinates
u_r, u_θ, u_z	Velocities in cylindrical coordinates
u_r, u_θ, u_ϕ	Velocities in spherical coordinates
\underline{u}, u_i	Fluid velocity vector
u_{Ni}	Velocity of component N in direction i
u_r, u_θ	Velocity components in polar coordinates
u_d	A non-dimensional velocity
u_s	Shock velocity
u^*	Friction velocity
U, U_i	Fluid velocity and velocity vector in absence of particle
U	Reference or upstream fluid velocity
U_∞	Velocity of upstream uniform flow
\mathcal{U}	Body force potential
v	Volume of particle, droplet or bubble
V, V_i	Absolute velocity and velocity vector of particle
V	Volume
V	Control volume
\dot{V}	Volume flow rate
w	Dimensionless relative velocity, W/W_∞
w	Work done per unit mass
Δw	Increment of work done per unit mass
W, W_i	Relative velocity of particle and relative velocity vector
W_∞	Terminal velocity of particle
W_p	Typical phase separation velocity
W_t	Typical phase mixing velocity
\dot{W}	Rate of work done on the fluid
We	Weber number, $2\rho W^2 R/S$
\mathcal{W}	Rate of work done per unit mass
x, y, z	Cartesian coordinates
x	Mass fraction
X, Y, Z	Displacements in x, y, z directions
x_i	Position vector
X_i	Displacement vector
\mathcal{X}	Mass quality
y	Elevation

z

Coordinate measured vertically upward

Greek Letters

α	Volume fraction
α_L	Thermal diffusivity of liquid
β	Volume quality
γ	Ratio of specific heats of gas
$\dot{\gamma}$	Shear rate
δ	Boundary layer thickness
δ_d	Damping coefficient
δm	Fractional mass
δ_T	Thermal boundary layer thickness
δ_2	Momentum thickness of the boundary layer
δ_{ij}	Kronecker delta: $\delta_{ij} = 1$ for $i = j$; $\delta_{ij} = 0$ for $i \neq j$
ϵ	Fractional volume
ϵ	Coefficient of restitution
ϵ	Rate of dissipation of energy per unit mass
ζ	Attenuation or amplification rate
η	Efficiency
η	Bubble population per unit liquid volume
θ	Angular coordinate or direction of velocity vector
θ	Reduced frequency
θ_w	Hopper opening half-angle
κ	Bulk modulus of compressibility
κ	Wavenumber
κ_L, κ_G	Shape constants
λ	Wavelength
λ	Mean free path
λ	Kolmogorov length scale
Λ	Integral length scale of the turbulence
Λ	Lame constant
Λ	Second coefficient of viscosity
μ	Dynamic viscosity
μ^*	Coulomb friction coefficient
ν	Kinematic viscosity
ν	Mass-based stoichiometric coefficient
ξ	Particle loading
ρ	Density of fluid
ϕ	Velocity potential
ϕ	Internal friction angle
ϕ	Flow coefficient, $j/\Omega r_d$
$\phi_L^2, \phi_G^2, \phi_{L0}^2$	Martinelli pressure gradient ratios
φ	Fractional perturbation in bubble radius
Φ	Rate of dilation
Φ^*	Dilation

ψ	Stream function
ψ	Head coefficient, $\Delta p^T / \rho \Omega^2 r_d^2$
σ	Cavitation number
σ_i	Inception cavitation number
σ_{ij}	Stress tensor
σ_{ij}^D	Deviatoric stress tensor
Σ	Poisson's ratio
$\Sigma(T)$	Thermodynamic parameter
τ	Kolmogorov time scale
τ_i	Interfacial shear stress
τ_n	Normal stress
τ_s	Shear stress
τ_w	Wall shear stress
ω	Radian frequency
ω_a	Acoustic mode frequency
ω_i	Instability frequency
ω_n	Natural frequency
ω_m	Cloud natural frequencies
ω_m	Manometer frequency
ω_p	Peak frequency
ω	Magnitude of vorticity
ω_i	Vorticity vector
ω_{ij}^*	Rate of rotation tensor
$\underline{\omega}, \omega_i$	Vorticity vector
ω_n	Natural frequency
Ω	Rotating frequency (radians/sec)
Ω_j	Unit direction vector ????????
Ω_{ij}	Rotation tensor

Subscripts

On any variable, Q :

Q_o	Initial value, upstream value or reservoir value
Q_1, Q_2, Q_3	Components of Q in three Cartesian directions
Q_1, Q_2	Values upstream and downstream of a component or flow structure
Q_∞	Value far from the particle or bubble
Q_A	Pertaining to a general phase or component, A
Q_b	Pertaining to the bulk
Q_B	Pertaining to a general phase or component, B
Q_B	Value in the bubble
Q_c	Critical values and values at the critical point
Q_C	Pertaining to the continuous phase or component, C
Q_C	Critical value
Q_D	Denotes design value
Q_D	Pertaining to the disperse phase or component, D
Q_e	Equilibrium value or value on the saturated liquid/vapor line

Q_e	Effective value or exit value
Q_E	Equilibrium value
Q_G	Pertaining to the gas phase or component
Q_i	Components of vector Q
Q_{ij}	Components of tensor Q
Q_L	Pertaining to the liquid phase or component
Q_m	Maximum value of Q
Q_M	Mean or maximum value
Q_N	Nominal conditions
Q_N	Pertaining to a general phase or component, N
Q_O	Pertaining to the oxidant
Q_r	Component in the r direction
Q_s	A surface, system or shock value
Q_S	Pertaining to the solid particles
Q_S	Pertaining to the surface
Q_V	Pertaining to the vapor phase or component
Q_w	Value at the wall
Q_θ	Component in the θ direction

Superscripts and other qualifiers

On any variable, Q :

Q_*	Throat values
Q', Q'', Q^*	Used to differentiate quantities similar to Q
\bar{Q}	Mean value of Q or amplitude of Q or complex conjugate of Q
\hat{Q}	Small perturbation in Q
δQ	Small change in Q
\tilde{Q}	Complex amplitude of oscillating Q
\dot{Q}	Time derivative of Q
\ddot{Q}	Second time derivative of Q
$\hat{Q}(s)$	Laplace transform of $Q(t)$
\check{Q}	Coordinate with origin at image point
$Re\{Q\}$	Real part of Q
$Im\{Q\}$	Imaginary part of Q

Units

In most of this book, the emphasis is placed on the nondimensional parameters that govern the phenomenon being discussed. However, there are also circumstances in which we shall utilize dimensional thermodynamic and transport properties. In such cases the International System of Units will be employed using the basic units of mass (kg), length (m), time (s), and absolute temperature (K).